

05-04-00

09/530931 PCT #

410 Rec'd PCT/PTO 02 MAY 2000 US

PCT Applicant's Guide - Volume II - National Chapter - US

Annex US.II, page 1

Express Mail No. EL634501753US

FORM PTO-1396  
(REV 10-95)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

03394.P003

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

INTERNATIONAL APPLICATION NO.  
PCT/IL98/00427INTERNATIONAL FILING DATE  
September 2, 1998

PRIORITY DATE CLAIMED

TITLE OF INVENTION

APPARATUS AND METHODS FOR CONNECTING A NETWORK USER TO A NETWORK SERVICE

APPLICANT(S) FOR DO/EO/US

Meir Alter

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b)) and PCT articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2)).
  - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ has been transmitted by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
  - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

## Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.  
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A subsequent specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

formal drawings submittal; (6) drawings sheets; international search report; copy of complete application w/amended claims (22 pages)

US

Annex US.II, page 2 PCT Applicant's Guide - Volume II - National Chapter - US

U.S. APPLICATION NO. <b>09/530931</b>	INTERNATIONAL APPLICATION NO. <b>PCT/IL98/00427</b>	ATTORNEY'S DOCKET NUMBER <b>03394.P003</b>
---------------------------------------	--	---

**17. ☒ The following fees are submitted:**

**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :**

Neither international preliminary examination fee (37 CFR 1.482 nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by EPO or JPO . . . . \$**970.00**

International preliminary examination fee (37CFR1.482)not paid to USPTO but International Search Report prepared by the EPO or JPO. . . . \$**840.00**

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee paid to USPTO (37 CFR 1.445(a)(2)) . . . . \$**760.00**

International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) . . . . \$**670.00**

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) . . . . . \$**96.00**

**ENTER APPROPRIATE BASIC FEE AMOUNT =**

Surcharge of \$ <b>130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).	\$	970.00
---	----	--------

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total claims	24 - 20 =	4	X \$18.00	\$	72.00
Independent claims	5 - 3 =	2	X \$78.00	\$	156.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$	1198.00
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$	
<b>SUBTOTAL =</b>				\$	1198.00
Processing fee of \$ <b>130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
<b>TOTAL NATIONAL FEE =</b>				\$	1198.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$ <b>40.00</b> per property +				\$	
<b>TOTAL FEES ENCLOSED =</b>				\$	1198.00
				\$ Amount to be refunded	\$
				\$ charged	\$

a. ☒ A check in the amount of \$ 1198.00 to cover the above fees is enclosed.


b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \$ \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 022666. A duplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

**Blakely, Sokoloff, Taylor & Zafman LLP**  
12400 Wilshire Blvd. 7th Floor  
Los Angeles, CA 90025-1026

  
 SIGNATURE  
**Eric S. Hyman**  
 NAME

30,139  
 REGISTRATION NUMBER

6/PART

09530909/530931  
422 Rec'd PCT/PTO 22 MAY 2000

Atty. Docket No.: 03394.P003  
Express Mail #: EL634501753US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re the application of: )  
Meir Alter )  
For: APPARATUS AND METHODS FOR CONNECTING A NETWORK )  
USER TO A NETWORK SERVICE )

SUBMISSION OF FORMAL DRAWINGS

Assistant Commissioner for Patents  
Washington, D.C. 20231


Dear Sir:

Submitted herewith is Figure 1-7 in connection with the above-identified application.

Respectfully submitted,

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Dated: 5/2/2000

  
Eric S. Hyman, Reg. No. 30,139

12400 Wilshire Boulevard, Seventh Floor  
Los Angeles, California 90025  
(310) 207-3800





FIG. 2

70



3/6

FIG. 3




FIG. 4




FIG. 5






FIG. 6





6/6

FIG. 7



6/PART

APPARATUS AND METHODS FOR CONNECTING A NETWORK USER TO A NETWORK SERVICE PROVIDER

5

## FIELD OF THE INVENTION

The present invention relates to apparatus and methods for connecting a user to a network such as the Internet, and in particular to providing connections between users and ISPs (Internet Service Providers).

10

## BACKGROUND OF THE INVENTION

15

A plethora of ISPs (Internet service providers) are in operation which provide access to the Internet. Users must sign up with each ISP directly and cannot switch between ISPs on the fly.

20

It is well-known in the art for an ISP to provide its own POP (point of presence) in every local area where the ISP wishes to provide connection service for individual users. Typically, the ISP establishes, for each POP, an office including a defined number of telephone lines, each telephone line being associated with a modem, an ISDN connection, or similar terminal equipment, and each telephone line being intended to support a single individual user dial-in connection. Typically, multiplexing equipment, routing equipment, and other communications equipment is provided locally at the POP to complete the connection between the individual user and the Internet.

25

The RADIUS (Remote Authentication Dial In User Service) protocol, described in RFC 2138 and RFC 2139, both dated April 1997 and both published by the Internet Engineering Task Force can be used to remotely authenticate a dial-in user of a computer service.

30

IP addressing rules related to the field of the present invention are described in RFC 1918 of the Internet Engineering Task Force.

Inverse Network Technology, Inc. generates performance profiles for various Internet Service Providers.

ISP Alliance, Inc. provides a shared cost, transparent services system which allows a subscriber to provide Internet services to customers without actually

**WO 00/14919**

**PCT/IL98/00427**

having the infrastructure to provide the Internet services.

The disclosures of all references mentioned above and throughout the present specification are hereby incorporated herein by reference.

WO 00/14919

PCT/IL98/00427

## SUMMARY OF THE INVENTION

The present invention seeks to provide improved apparatus and methods for connecting a user to a network such as the Internet.

5 There is thus provided in accordance with a preferred embodiment of the present invention a system for connecting to Internet service providers via networking circuitry, the system including a user interface operative to accept a user's choice of an Internet service provider from among a plurality of Internet service providers and a configurator operative to connect the user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.

10 The user interface may include a web-based display. The term "web-based display" is used throughout the present specification and claims to refer to an HTML (Hypertext Markup Language) or similar page that may be viewed by a standard WWW browser or a similar program.

15 The user interface may include a display of at least some of the plurality of Internet service providers.

Preferably, initial communications between user and the system of the present invention, until selection of an ISP by the user, are carried out using IP protocol and the server of the system allocates an internal IP address to the user. Once the user selects an ISP, a second IP address is allocated to the user, from among a pool of IP addresses belonging to the selected ISP. The second IP address is used, typically via network address translation (NAT) as is well known in the art, as an external address representing the user to the Internet. The internal IP address is typically retained by the user until logging out of the system or hanging up the connection.

25 Preferably, a telephone company allocates to the system of the present invention a local number which any subscriber can dial. The subscriber connects to the system of the present invention via the telephone company and a conventional modem. Typically, the telephone company subscriber's telephone number functions as his or her login/password and no additional password need be assigned to him or her.

30 Preferably, the telephone company subscriber is billed for use of the system of the present invention, as part of their telephone bill, similar to billing of other special services provided over the telephone such as long distance service. The subscriber therefore does not need to provide his or her credit card number.

WO 00/14919

PCT/IL98/00427

Also provided, in accordance with a preferred embodiment of the present invention, is a method for connecting to Internet service providers via networking circuitry, the method including displaying a list of a plurality of Internet service providers to a user, accepting a user's choice of an Internet service provider  
5 from among the plurality of Internet service providers, and connecting the user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.

There is also provided in accordance with another preferred embodiment of the present invention a system for connecting to Internet service providers via  
10 networking circuitry, the system including a user interface operative to display information regarding a plurality of Internet service providers including quality of service information and to accept a user's choice of an Internet service provider from among the plurality of Internet service providers, thereby to define a user-selected Internet service provider, and a configurator operative to connect the user to the user-  
15 selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.

Further in accordance with a preferred embodiment of the present invention the user interface includes a web-based display.

Still further in accordance with a preferred embodiment of the present  
20 invention the user interface includes a display of at least some of the plurality of Internet service providers.

Additionally in accordance with a preferred embodiment of the present invention the system also includes user identification apparatus operative to identify the  
25 user.

Moreover in accordance with a preferred embodiment of the present invention the user identification apparatus is operative to identify the user based on a telephone number used by the user to establish a connection with the system.

There is also provided in accordance with another preferred embodiment of the present invention a method for connecting to Internet service providers via  
30 networking circuitry, the method including displaying information regarding a plurality of Internet service providers including quality of service information, accepting a user's choice of an Internet service provider from among the plurality of Internet service providers, thereby to define a user-selected Internet service provider, and connecting the

WO 00/14919

PCT/IL98/00427

user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.

There is also provided in accordance with another preferred embodiment of the present invention a virtual point of presence (POP) including a routing center  
5 operative to communicate with a network user and with at least one Internet Service Provider (ISP) and to route communications therebetween, and an authentication and ISP routing center receiving an identification of the network user from the routing center and operative to authenticate the network user based, at least in part, on the identification of the network user, and to choose an ISP and to communicate an ISP  
10 identification identifying the ISP to the routing center, the routing center being operative, upon receipt of the ISP identification, to route communications from the network user to an ISP associated with the ISP identification.

Further in accordance with a preferred embodiment of the present invention the authentication and ISP routing center is operative to choose the ISP based  
15 on a telephone number of the network user.

Further in accordance with a preferred embodiment of the present invention the authentication and ISP routing center is operative to choose the ISP based, at least in part, on at least one of the following a telephone number of the network user, identifying information of the network user, and profile information of the network user.

Further in accordance with a preferred embodiment of the present invention the routing center is also operative to maintain accounting records of routing  
20 services performed for the network user and the ISP.

There is also provided in accordance with another preferred embodiment of the present invention a method for providing a virtual point of presence (POP) using a  
25 network routing center, the method including providing communications, from the network routing center, with a network user and with at least one Internet Service Provider (ISP), receiving an identification of the network user from the routing center, authenticating the network user based, at least in part, on the identification of the network user, choosing an ISP and communicating an ISP identification identifying the  
30 ISP to the routing center, and routing communications from the network user to an ISP associated with the ISP identification.

Further in accordance with a preferred embodiment of the present invention the method also includes storing utilization information in a database.

WO 00/14919

PCT/IL98/00427

Still further in accordance with a preferred embodiment of the present invention the method also includes producing a report based on the utilization information.

There is also provided in accordance with another preferred embodiment of the present invention a payment processing method for processing payments over a network, the network including a routing center for routing communications between at least one user and at least one service provider, the method including establishing a connection, through the routing center, between a user and a service provider, routing communications, at the routing center, between the user and the service provider, requesting, through the service provider, an item associated with a payment, initiating, at the routing center, an authorization of the payment, and receiving, at the routing center, billing information including a request to pay the payment.

Further in accordance with a preferred embodiment of the present invention the method also includes paying the requested payment from the routing center.

Still further in accordance with a preferred embodiment of the present invention the paying step includes aggregating a plurality of requested payments into a single payment.

Additionally in accordance with a preferred embodiment of the present invention the service provider includes an Internet service provider (ISP), and the requesting step includes requesting an item from a World Wide Web (WWW) site.

Moreover in accordance with a preferred embodiment of the present invention the system includes an on-the-fly ISP performance monitor operative to monitor performance of at least one ISP on the fly and to supply at least one quality of service parameter to the user interface for display.

Further in accordance with a preferred embodiment of the present invention the system also includes an infrastructure leaser operative to lease network infrastructure to at least one Internet service provider.

Additionally in accordance with a preferred embodiment of the present invention the infrastructure leaser is operative to lease network infrastructure to at least one Internet service provider from among the plurality of Internet service providers.

Moreover in accordance with a preferred embodiment of the present invention the system also includes a resource utilization monitor operative to record

WO 00/14919

PCT/IL98/00427

information regarding occurrence of at least one of the following situations with respect to network infrastructure leased by at least one Internet service provider: underutilization of the infrastructure leased by the at least one Internet service provider, and overutilization of the infrastructure leased by the at least one Internet service provider.

5

Further in accordance with a preferred embodiment of the present invention the recording step is performed on the fly.



## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated from the following detailed description, taken in conjunction with the drawings in which:

5 Fig. 1 is a simplified block diagram of apparatus, constructed and operative in accordance with a preferred embodiment of the present invention, for connecting a user to the Internet via any user-selected ISP from among a plurality of ISPs;

Fig. 2 is an example of a screen display of the home user's computer of Fig. 1;

10 Fig. 3 is a simplified flowchart illustration of a preferred method of operation for the apparatus of Fig. 1;

Fig. 4 is a simplified block diagram illustration of apparatus for providing a virtual POP (point of presence) to an ISP, the apparatus being constructed and operative in accordance with another preferred embodiment of the present invention;

15 Fig. 5 is a simplified flowchart illustration of a preferred method of operation of the apparatus of Fig. 4;

Fig. 6 is a simplified block diagram illustration of a preferred embodiment of the routing center of Fig. 4; and

20 Fig. 7 is a simplified flowchart illustration of a preferred method of operation of the apparatus of Fig. 1 or the apparatus of Fig. 4.

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference is now made to Fig. 1 which is a simplified block diagram of apparatus 15, constructed and operative in accordance with a preferred embodiment of the present invention, for connecting a user to the Internet via any user-selected ISP from among a plurality of ISPs 10.

As shown, the apparatus of Fig. 1 includes the following sub-systems:

An authentication server 14 that validates if the user can use the service;

An accounting server/manager 20 that monitors the start and end of the connections to the service and to a specific ISP 10;

An IP address manager 30 that allocates and collects back IP addresses of each ISP 10. Typically, each ISP allocates a typically static pool of available IP addresses from the IP address pool assigned to that ISP and communicates information including the available IP addresses to the IP address manager 30 by any appropriate means. The IP address manager 30 keeps track of the available IP addresses for each ISP and allocates an appropriate IP address on demand. When a user disconnects from the ISP the IP address manager preferably reclaims the address for future users;

A router configuring engine 40 that configures the router 50 in order to connect the user to a desired ISP 10; and

A network access server (NAS) 60 is operative to generate an appropriate user interface, preferably a GUI (graphical user interface) that presents the user with the ISP 10 and their rates and enables the user to choose an ISP 10, change an ISP 10 and elect to disconnect from an ISP 10. Typically, the GUI comprises an HTML file sent by the NAS 60 to the computer 70 of the home user(VIA A NETWORK 80?). This HTML file is typically rendered as a GUI screen by the web browser of home computer 70.

Typically, the GUI displays to the user the speed of each ISP's connection to the Internet, where the displayed speed is preferably the actual speed from the user's perspective, but may alternatively comprise one or more speeds of components of the ISP's network.

Preferably, the GUI displays some or all of the following options:

1. Connect to fastest ISP.

WO 00/14919

PCT/IL98/00427

2. Connect to cheapest ISP.
3. Connect to most cost-effective ISP.

Preferably, an ISP performance manager 90 is provided which monitors the performance level of each ISP 10 and generates quality of service statistics. The results are typically aggregated by time and statistics for the last measured period are typically shown to the user. Actual performance of an IDS may typically be based on the time required for the ISP performance manager 90 to perform a predefined set of tasks, such as retrieving specified Internet information or executing an Internet ping, through each ISP 10. Under this definition of actual performance, a shorter time to complete the task indicates greater actual performance.

Preferably, each ISP is provided with an ISP manager which allows each ISP to collect information such as currently connected user report, port monitoring, accounting and billing information.

Fig. 2 is an example of a screen display which may be generated by the GUI of NAS 60. As shown, the screen display includes a list of a plurality of ISPs 10 plus comparative data regarding each of the ISPs, thereby allowing a user to make an intelligent choice, for example, by pressing the appropriate "Connect" screen button.

Fig. 3 is a simplified flowchart illustration of a preferred method of operation for the apparatus of Fig. 1. As shown, in step 110, the user initially connects to NAS (Network Access Server) 60 (Fig. 1) via a network 80 such as a PSTN (Public Switched Telephone Network) or via the ISDN (Integrated Services Digital Network).

In step 120, the NAS 60 authenticates the user, using a suitable protocol such as the RADIUS (Remote Authentication Dial In User Service) protocol, which protocol is well-known in the art and is described in RFC 2138 and RFC 2139, both dated April 1997 and both published by the Internet Engineering Task Force. The authentication may succeed, for example, if:

- a. the number called by the user is that of the central service, it being well known in the art, in the case of telephone numbers dedicated to a single ISP, to have a global service telephone number for Internet access, the global number being used from any location and switching to a local point of service being automatically accomplished; the present invention provides an analogous service for multiple ISPs; and



1. Connect to fastest ISP.
2. Connect to cheapest ISP.
3. Connect to most cost-effective ISP.

In step 170, a RADIUS access-request message (including the selected  
 5 ISP) is sent by the NAS 60 to the authentication server 14. The message requests the  
 IP manager 30 to allocate an IP address for the connection, from the IP address pool  
 of the user-selected ISP 10.

In step 180, the router configuring engine 40 configures the NAT  
 (Network Address Translation) tables of the router 50 and the routing policies of the  
 10 router 50 using a suitable protocol such as HTTP (Hyper Text Transfer Protocol) for  
 communications therebetween.

From this time on, the user's IP frames are forwarded to the network of  
 the user-selected ISP 10 and the user can connect to the Internet. Therefore (step  
 190), at this time NAS 60 sends a RADIUS start-accounting message to  
 15 accounting manager 20.

At a suitable time (step 200), the user discontinues his connection to  
 the current ISP 10, e.g. by pushing the disconnect button or by choosing a different  
 ISP).

Following (step 210), NAS 60 sends a RADIUS stop-accounting  
 20 message to accounting manager 20.

Accounting manager 20 returns the IP address of the ISP 10 to the IP  
 address manager 30 (step 220).

When the user disconnects the call (step 230), the NAS 60 sends a  
 RADIUS stop accounting message to the accounting manager 20 (step 240). The  
 25 accounting manager 20 returns the IP addresses of the connection between the user and  
 the system of Fig. 1, described above as the first IP address, and the IP for  
 communication with the ISP 10, described above as the second IP address, to the IP  
 address manager 30 (step 250).

A particular advantage of a preferred embodiment of the present  
 30 invention is that each ISP need not establish a POP (point of presence) site in each  
 area code within the ISP's customer base. Also, each ISP need not install and maintain  
 its own billing and collecting system.



WO 00/14919

PCT/IL98/00427

for the user, is passed to the ISP routing server 260.

The ISP routing server 260 determines to which ISP 265 the user 270 should be connected. A determination of an ISP 265 may be based on the telephone number chosen by the user 270, such that, from the point of view of the user 270, the apparatus of Fig. 4 presents a virtual ISP which functions identically, to the user 270, to a real conventional ISP. The telephone number may be obtained using Dialed Number Identification System (DNIS), as is well known in the art, or by other appropriate means. Alternatively, the determination of the ISP may be based, for example, in whole or in part, on any one or combination of the following: the telephone number of the user 270, which may be determined by a caller identification method, as is well-known in the art; identifying information and/or further identifying information of the user 270; profile information for the user 270, the profile information typically being stored by the ISP routing server 260; by a domain name selected by the user 270, and based on information, typically stored by the ISP routing server 260, indicating which one or more ISPs is preferred for that domain; or any other appropriate information.

After the ISP routing server 260 has determined the one ISP 265 to which the user 270 should be connected, the AIR 252 communicates the identity of the ISP to the routing center 245. The routing center 245 then sets up an appropriate routing definition, as is well-known in the art, and routes IP packets between the user 270 and the ISP 265, transparently to the user 270 and the ISP 265. Thus a virtual user-ISP connection, virtual in the sense that the physical link between the routing center 245 and the ISP 265 can be used to establish many such connections for a plurality of users, is established between the user 270 and the ISP 265, and thus the apparatus of Fig. 4 acts effectively as a virtual POP.

Preferably, the routing center 245 is operative to maintain accounting records of all connections from any user 270 to any ISP 265, the accounting records and the apparatus and methods used for maintaining the accounting records typically being similar to those well-known in the art in telephone central office systems. Preferably, accounting records maintained by the routing center 245 are used to report usage and/or charges to each ISP 265, or to directly invoice each user 270, typically in accordance with rates and regulations established by each ISP 265, for usage of each ISP 265. Alternatively or additionally, the accounting records may be used to charge each ISP 265 for routing services provided.





WO 00/14919

PCT/IL98/00427

T1 or T3 lines.

Reference is now made to Fig. 6, which is a simplified block diagram illustration of a preferred embodiment of the routing center 245 of Fig. 4. It is appreciated, as described further below, that components of Fig. 6 may also be used in a preferred embodiment of the system of Fig. 1, to perform similar functions therein.

The apparatus of Fig. 6 preferably comprises a routing control unit 310. The routing control unit 310 may be operative, as described above with reference to Fig. 4, to perform the routing operations of the routing center 245 of Fig. 4.

The apparatus of Fig. 6 also preferably comprises a database subsystem 320 and a reporting subsystem 330. The database subsystem 320 and the reporting subsystem 330 may, if comprised in a preferred embodiment of the system of Fig. 1, be comprised, for example, in the accounting server 20 of Fig. 1, or in any other appropriate component of the system of Fig. 1.

The routing control unit 310, the database subsystem 320, and the reporting subsystem 330 are preferably implemented in any suitable combination of computer hardware and software, as is well-known in the art. The routing control unit 310, the database subsystem 320, and the reporting subsystem 330 are all preferably in operative communication with each other.

The operation of the apparatus of Fig. 6 is now briefly described. The routing control unit 310 reports its routing activities, typically but not necessarily including essentially all of its routing activities, to the database subsystem 320, which stores the reported activities in any appropriate database. Typically, routing activities reported include, for a combination of the operations of the system of Fig. 1 and the apparatus of Fig. 4, one or more of the following: user requests to connect to a particular ISP; automatic user connection to an ISP; length of user session; number of packets and/or bytes transferred during user session; charges allocated to users, ISPs, or others; and any other appropriate available information on the usage and operation of the system of Fig. 1 and/or the apparatus of Fig. 4.

The reporting system 330 is operative, typically upon receipt of a request from an administrative user of the system and/or periodically, to analyze some or all of the information comprised in the database maintained by the database subsystem 320 and to generate reports based thereon. It is appreciated that a very wide variety of reports could thus be generated. Some examples of information which might typically be






PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b>  <b>H04L</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 00/14919</b>  <b>(43) International Publication Date:</b> 16 March 2000 (16.03.00)
<b>(21) International Application Number:</b> PCT/IL98/00427 <b>(22) International Filing Date:</b> 2 September 1998 (02.09.98) <b>(71) Applicant (for all designated States except US):</b> N.C.C. EXPORT SYSTEMS 1995 LTD. [IL/IL]; Shenker Street 20, Kiryat Arie, 49513 Petach Tikva (IL). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> ALTER, Meir [IL/IL]; Shenker Street 20, Kiryat Arie, 49513 Petach Tikva (IL). <b>(74) Agents:</b> SANFORD, T., Colb et al.; Sanford T. Colb & Co., P.O. Box 2273, 76122 Rehovot (IL).		<b>(81) Designated States:</b> AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>

**(54) Title:** APPARATUS AND METHODS FOR CONNECTING A NETWORK USER TO A NETWORK SERVICE PROVIDER**(57) Abstract**

A system for connecting to Internet service providers via networking circuitry, the system including a user interface operative to display information regarding a plurality of Internet service providers including quality of service information and to accept a user's choice of an Internet service provider from among the plurality of Internet service providers, thereby to define a user-selected Internet service provider, and a configurator operative to connect the user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.



## CLAIMS

1. A system for connecting to Internet service providers via networking circuitry, the system comprising:
- 5 a user interface operative to display information regarding a plurality of Internet service providers including quality of service information and to accept a user's choice of an Internet service provider from among the plurality of Internet service providers, thereby to define a user-selected Internet service provider; and
- 10 a configurator operative to connect the user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.
2. A system according to claim 1 wherein the user interface comprises a web-based display.
- 15 3. A system according to claim 1 or claim 2 wherein the user interface comprises a display of at least some of the plurality of Internet service providers.
4. A system according to claim 1 or claim 2 and also comprising user identification apparatus operative to identify the user.
- 20 5. A system according to claim 4 and wherein the user identification apparatus is operative to identify the user based on a telephone number used by the user to establish a connection with the system.
- 25 6. A method for connecting to Internet service providers via networking circuitry, the method comprising:
- displaying information regarding a plurality of Internet service providers including quality of service information;
- 30 accepting a user's choice of an Internet service provider from among the plurality of Internet service providers, thereby to define a user-selected Internet service provider; and
- connecting the user to the user-selected Internet service provider by generating an on-the-fly configuration of the networking circuitry.

WO 00/14919

PCT/IL98/00427

7. A virtual point of presence (POP) comprising:

a routing center operative to communicate with a network user and with at least one Internet Service Provider (ISP) and to route communications therebetween;  
5 and

an authentication and ISP routing center receiving an identification of the network user from the routing center and operative:

to authenticate the network user based, at least in part, on the identification of the network user; and

10 to choose an ISP and to communicate an ISP identification identifying the ISP to the routing center,

wherein the routing center is operative, upon receipt of the ISP identification, to route communications from the network user to an ISP associated with the ISP identification.

15 8. Apparatus according to claim 7 and wherein the authentication and ISP routing center is operative to choose the ISP based on a telephone number of the network user.

20 9. Apparatus according to claim 7 wherein the authentication and ISP routing center is operative to choose the ISP based, at least in part, on at least one of the following: a telephone number of the network user; identifying information of the network user; and profile information of the network user.

25 10. Apparatus according to claim 7 and wherein the routing center is also operative to maintain accounting records of routing services performed for the network user and the ISP.

30 11. A method for providing a virtual point of presence (POP) using a network routing center, the method comprising:

providing communications, from the network routing center, with a network user and with at least one Internet Service Provider (ISP);

WO 00/14919

PCT/IL98/00427

receiving an identification of the network user from the routing center;  
 authenticating the network user based, at least in part, on the  
 identification of the network user;

5 choosing an ISP and communicating an ISP identification identifying the  
 ISP to the routing center; and

routing communications from the network user to an ISP associated with  
 the ISP identification.

10 12. A method according to claim 6 or claim 11 and also comprising:  
 storing utilization information in a database.

13. A method according to claim 12 and also comprising:  
 producing a report based on the utilization information.

15 14. A payment processing method for processing payments over a network,  
 the network comprising a routing center for routing communications between at least  
 one user and at least one service provider, the method comprising:

establishing a connection, through the routing center, between a user and  
 a service provider;

20 routing communications, at the routing center, between the user and the  
 service provider;

requesting, through the service provider, an item associated with a  
 payment;

25 initiating, at the routing center, an authorization of the payment; and  
 receiving, at the routing center, billing information including a request to  
 pay the payment.

30 15. A method according to claim 14 and also comprising:  
 paying the requested payment from the routing center.

16. A method according to claim 15 and also wherein the paying step  
 comprises:


















FIG. 1

FIG. 2

70

Disconnect!		Price/Performance		Fastest		Cheapest	
D		P		F		C	
(*) Actual Performance	1 Hr/USD	Connection Fee	Available ISP name list				
	\$ 0.1	-	Spiders				
	\$ 0.12	\$ 0.1	Gold Net				
	\$ 0.20	\$ 0.14	America On Line				
	\$ 0.12	\$ 0.1	GoldNet				
	\$ 0.12	-	Web Master Net				
	\$ 0.12	\$ 0.1	IBM Globe Net				
	\$ 0.20	\$ 0.1	Shark Net				
	\$ 0.14	\$ 0.1	Internet Master				
	\$ 0.12	-	FastCom				
	\$ 0.1	-	ATM Com				

Select an ISP which best suits your requirements, your phone bill will be charged.  
You have full access free of ISP subscription!

3/6

FIG. 3




FIG. 4




FIG. 5







FIG. 6



6/6

FIG. 7





09530931 041900

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or any original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### APPARATUS AND METHODS FOR CONNECTING A NETWORK USER TO A NETWORK SERVICE PROVIDER

the specification of which



is attached hereto.

was filed on September 2, 1998 as

United States Application Number \_\_\_\_\_

or PCT International Application Number \_\_\_\_\_

PCT/IL98/00427

and was amended on \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

#### Prior Foreign Application(s):

APPLICATION NUMBER	COUNTRY (OR INDICATE IF PCT)	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below:

APPLICATION NUMBER	FILING DATE

22-AUG-2000 TUE 13:34

M.C.C. 972 3 9221584  
S. T. COLB & CO.  
972 8 9454556

FAX NO. 972 8 9454556

SEP 03 11:37 PM '00  
03703

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION NUMBER	FILING DATE	STATUS (ISSUED, PENDING, ABANDONED)

5/- I hereby appoint BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, a firm including: William E. Alford, Reg. No. 37,701; Farzad F. Amini, Reg. No. 42,261; Amy M. Armstrong, Reg. No. 42,265; Abayinua T. C. Ayieyimg, Reg. No. 33,412; William Thomas Bubbitt, Reg. No. 39,521; Carol F. Barry, Reg. No. 41,600; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Beroznik, Reg. No. 33,474; Michael A. Bernadecou, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Ronald C. Card, Reg. No. 44,587; Thomas M. Coester, Reg. No. 39,637; Donna Jo Coningaby, Reg. No. 41,684; Michael Anthony Dusanctis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Robert Andrew Diehl, Reg. No. 40,922; Matthew C. Fagan, Reg. No. 37,542; Tarek N. Fahmi, Reg. No. 41,802; Paramita Ghosh, Reg. No. 42,806; James Y. Go, Reg. No. 40,621; James A. Henry, Reg. No. 41,064; William F. Holloway III, Reg. No. 41,845; Cheryl Sue Holloway, Reg. No. 37,850; George W. Hoover II, Reg. No. 32,992; Eric S. Hynum, Reg. No. 30,139; William W. Kidd, Reg. No. 31,772; Sang Hai Kim, Reg. No. 40,450; Eric T. King, Reg. No. 44,188; Erica W. Kuo, Reg. No. 42,774; Michael J. Mallic, Reg. No. 36,591; Paul A. Mendonca, Reg. No. 42,879; Darren J. Milliken, Reg. No. 42,004; Chun M. Ng, Reg. No. 36,878; Thien T. Nguyen, Reg. No. 43,835; Thinh V. Nguyen, Reg. No. 42,034; Dennis A. Nicholls, Reg. No. 42,036; Lisa A. Norris, Reg. No. 44,976; Daniel E. Ovanorun, Reg. No. 41,236; William F. Ryan, Reg. No. 44,313; James H. Sutter, Reg. No. 35,668; William W. Schmal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Jeffrey S. Smith, Reg. No. 39,377; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Judith A. Szepiet, Reg. No. 39,393; Vincent P. Tassinad, Reg. No. 42,179; Edwin H. Taylor, Reg. No. 25,129; Joseph A. Twumowski, Reg. No. 42,191; Lester J. Vincent, Reg. No. 31,460; Glenn R. Von Tersch, Reg. No. 41,364; John Patrick Ward, Reg. No. 40,216; Charles T. J. Wolgell, Reg. No. 43,398; James M. Wu, Reg. No. 45,241; Steven D. Yuter, Reg. No. 42,242; and Norman Zafman, Reg. No. 26,250; my attorney, and Andrew C. Chen, Reg. No. 43,544; Justin M. Dillon, Reg. No. 42,486; and John F. Travis, Reg. No. 43,203; my patent agents, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (310) 207-3800, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor (given name, family name)

Meir Alter

Inventor's Signature X

Date 24.8.00

Residence

49513 Petach Tikva, Israel  
(City & State)

Citizenship

Israel  
(Country)

P. O. Address

Shenker Street 20, Kiryat Arich

49513 Petach Tikva, Israel

Docket No. 03394.1003

Pg 2